

技术资料

VPS250 2.5 m 电压探头组 75 MHz



主要特性

产品概述: VPS250 2.5 m 电压探头组 75 MHz

Double insulated voltage probe

产品规格: VPS250 2.5 m 电压探头组 75 MHz

General Specifications	
Attenuation	10x
Bandwidth	75 MHz
Max. input voltage	1000 V
Max. voltage to ground	600 V CAT III, 1000 V CAT II per IEC / EN61010-31
Input resistance	10 Mohm
Input capacitance	18.5 pF

Compensation range	10 to 35 pF
Cable Length	2.5 m
BB120 Shielded Banana to BNC Adapter is required to adapt to ScopeMeter 120 Series shielded banana jack inputs.	

型号



Fluke VPS250

VPS250 2.5 m 电压探头组 75 MHz

Each probe set includes:

- 600 V CAT III / 1000 V CAT II rated
- 10:1 Voltage probe
- Hook clip for probe tip, 4-mm test probe for probe
- Ground lead with hook clip
- Ground lead with mini alligator
- One year warranty

Fluke. 让您的工作畅通无阻。

福禄克测试仪器（上海）有限公司 电话：400-810-3435 ©2024 福禄克公司
11/2024

北京福禄克世禄仪器维修和服务有限公司 电
话：400-615-1563 未经许可，本文档禁止修改
福禄克测试仪器（上海）有限公司上海维修中心 电
话：021-54402301, 021-54401908分机269
福禄克测试仪器（上海）有限公司深圳第一特约维修点
电话：0755-86337229