M9506A High-Performance, 5-slot AXIe Chassis PCIe Gen 3, 16 GB/s slot BW, up to 300 W/slot





DATA SHEET

Find us at www.keysight.com

Introduction

The Keysight Technologies, Inc. M9506A is a high-performance AXIe chassis and is the best choice for demanding, modular applications. The chassis is compliant with the AXIe 1.0 Rev 3.0 Wide-AXIe specification. It provides 5 slots for AXIe instrument modules, up to 300 watts per slot, and includes an embedded system module that does not take up an instrument slot. The embedded system module (ESM) provides a Gen 3 x8/x16 PCIe[®] interfaces for connecting the chassis to an external controller or expanding the system using multiple chassis. To minimize rack space, the instrument module slots are arranged horizontally. The chassis is the quietest AXIe chassis available with its new cooling design.



Key features

- Five x16 Gen 3 slots compliant to AXIe 1.0 Revision 3 (AXIe-wide)
- Embedded system module with flexible, dual Gen 3 x8 PCIe interface for high data BW and multichassis configurations
- Thunderbolt[™] 3 interface provides an alternative connection to a Thunderbolt-equipped laptop or desktop computer and doesn't require a PC interface card in most cases
- 62 differential, high-bandwidth local bus lines provide very large data path between adjacent modules
- High-performance, push-pull cooling system increases airflow while decreasing fan noise
- High-power with up to 300 W cooling per slot
- Open Zone 3 for system customization
- Multi-chassis power-sequencing and front panel external trigger inputs/outputs for multi-chassis synchronization
- Front-removable fan trays
- GPS synchronization and time stamping option (M9506A-GP1)
- Optional integrated backside controller for digitizers (M9506A-BC1), enabling secure SCPI over LAN functionality

Backplane Configuration

The M9506A provides a Gen 3 x16 PCIe linked to each instrument along with a high-performance local bus, GbE LAN fabric, DC power rail, and triggering lines.



Figure 1. M9506A AXIe chassis backplane



Figure 2. Backplane block diagram

Embedded System Module (ESM)

The M9506A AXIe chassis utilizes an embedded system module to perform the chassis management functions contained in the AXIe specification. In addition, the ESM also provides external clock and trigger in/out connectors for system synchronization. It can be connected to the host using either a Gen 3 x8/x16 PCIe or Thunderbolt 3 cable. The front panel x8 PCIe connectors are disabled when using the Thunderbolt connection.



Figure 3. M9506A ESM block diagram

Open Zone 3

The M9506A chassis provides access to the Zone 3 defined in the AXIe standard. Access to Zone 3 is achieved by removing back panel and backplane covers. This will access to the Zone 3 area on modules in slots 2-5 and is perfect for applications such as running cable to the back of AXIe modules.



Figure 4. M9506A Zone 3 access

GPS Synchronization and Timestamping (option M9506A-GP1)

The M9506A-GP1 option adds GPS synchronization ability along with an external antenna port on the front panel. It provides an accurate 1 PPS output and the 10/100 MHz reference can be locked to this clock. The PPS signal can be propagated to trigger I/O and trigger events can be timestamped. Other GPS information is also provided including latitude, longitude, and altitude.

Integrated Backside Controller for Digitizer Modules (option M9506A-BC1)

Test system security is a challenge that many Aerospace and Defense (AD) customers face. The open operating systems found in current test equipment is a vulnerability point that requires significant management and overhead. Additionally, many of these customers prefer the ease of use of traditional benchtop equipment which have LAN interfaces, SCPI programming, and historically had closed operating systems.

Option -BC1 was developed to enhance security for high channel count digitizer applications, bringing the ease of use of traditional benchtop together with the benefits of a modular platform. A simple LAN connection gives you easy SCPI based control of many channels in a small space.

- Ease of use of traditional benchtop
 - o LAN Interface
 - SCPI programming
 - Closed OS
- Benefits of modular platform
 - Performance
 - Channel density
 - Power consumption / cable management

Option -BC1 adds a closed, instrument-grade, Linux-based controller to the back of the M9506A chassis. It includes the necessary software layers (i.e. VISA / HiSLIP server, SCPI parser, Linux instrument driver) for SCPI over LAN control of the M9703B, M9710A, and M9709A digitizers. (see Figure 5).



Figure 5. Conceptual block diagram for M9506A-BC1. Support of additional HW simply requires additional software

Software Platform

Driver

The M9506A chassis comes complete with IVI. NET, IVI-C, and LabVIEW drivers. Windows 7, 8.1, and 10 operating systems are supported, and applications can be created using a variety of software tools including LabVIEW, LabWindows/CVI, MATLAB, VEE, Visual Basic, VisualStudio.NET (C/C++, C#, VB.NET).

Chassis Web Interface

The AXIe chassis includes a built-in Web interface for configuration, control, and monitoring of the chassis (Figure 6). This interface can be accessed by either LAN or PCIe.

	506A AXIe 5 Slot Chassis										
Home Module Configuration	on Fan Control E-keying Configure L/	AN He	alth 😲		XI 5 (21.1.1	01				
		1105		A A 01234	XIE 5 3	Slot (Chase	SIS			
	Connected to AXIe	e M950	J6A chassi	S						-	
	at IP address 141.183.1	89.112		Fan	Control	E-keyi	ng C	onfigure LAN	Health 🧲	,	
And the state of the state	Turn On Front Panel Identific	ation Indic	ator								
							Normal				
							Normal				
Description							35				
Model number	M95064			_ =							
Monufacturer	Kaveight Tachnologies						35	1 % of m	iaximum RPM	6	
Sarial number	0122456780	A KE	HNOLOGIES Serial number	6A AXIe 5	Slot Cha	ssis					
	CEAX 1 0.00 0007 40000 R0500 C	1 Marca	Made da Carella unifera	Fac Cooked	- E tandan	Contrast	-1.01	death 0			
Armware revision	POAX-1.0.09-0007-A0009-B0009-C0	E Plome	Module Configuration	Fan Control	E-keying	Consigur	e LAN	Heath U			
Jescription	M9500A AXIE 5 SIDE Chassis										
Host ID	PCSERNO,LK42477582	Chassi	is Health								
License Option	Full Range	Sensor	rs								
More Information		Module	Instrument		State	Senso	or Readin	igs			
		5	AXIe System Controlle	r	Active						
			Status		_	ID Ty	pe	Name	Lower Critical	Reading	Upper Critical
			Nominal			7 Ve	stage	SYSTEM 3.30V MG	3.00 Volts	3.28 Volts	3.64 Volts
			Nominal			8 Vo	stage	SYSTEM 3.3V	3.00 Volts	3.44 Volts	3.64 Volts
			Nominal			9 Ve	sitage	PEX 1.8V	1.64 Volts	1.76 Volts	1.98 Volts
			Nominal			10 Ve	oltage	XILINUX 1.2V MGT	1.08 Volts	1.18 Volts	1.32 Volts
			Nominal			11 Ve	stage	AILINUX 1.2V	0.78 Volts	1.18 Volts 0.90 Volts	1.32 Volts
			Nominal			13 Vc	sitage	0.9V_A 8749	0.78 Volts	0.88 Volts	1.00 Volts
			Nominal			14 Vo	oltage	0.9V 8749	0.78 Volts	0.90 Volts	1.00 Volts
			Nominal			15 Te	mperature	IPMC Temp	-5.00 degrees C	27.00 degrees C	75.00 degrees C
			Nominal			16 Te	emperature	PSU3 Temp	-5.00 degrees C	29.00 degrees C	75.00 degrees C
			Nominal			17 Te	mperature	GPIB EPGA Terro	-5.00 degrees C	30.00 degrees C 29.00 degrees C	75.00 degrees C
			Nominal			19 Te	mperature	PLX8718 Temp	-5.00 degrees C	29.00 degrees C	65.00 degrees C
			Alexandered					Di Marza Tama	0.00 4 0	00.00 400000	00.00 4

Figure 6. M9506A Web interface

Soft Front Panel Interfaces

Two Soft Front Panel (SFP) interfaces to monitor and control the AXIe chassis are provided with the M9506A driver. Both SFPs use the IVI driver for communications with the chassis.

- The chassis monitoring SFP has some of the basic functionality of the chassis Web page and allows the user to review numerous performance characteristics such as fan speeds, chassis temperatures, and power supply operating conditions. The monitoring SFP is shown in Figure 7.
- The triggering SFP provides an interface to the chassis triggering subsystem and simplifies triggering setup. The trigger SFP is shown in Figure 8.

111	Keysi	ght M9506A /	AXIe Chassis SFP	1.0.21.0								-					
Fi	e Utili	ties Tools	Help														
	Turn Or	n Indicator Lig	lht									Serial Num	ber: MY12345678	e e			
	Fans	Chassis	Power Supply	PCIe Link Slot	View												
[💷 Keysi	ght M9506A /	AXIe Ch	assis SFP 1	1.0.21.0				_		×
			Fan	Current Speed	(RPM) Ala	rm Occurred	File Utili	ities Tools	Help								
			Fan 0	3840	0	Nominal	Turn O	n Indicator Lic	aht					c	Serial Number	· MV123	45678
			Fan 1	3720	0	Nominal	Eane	Chassis	Powe	r Supply	PCIe Link	Slot View				. 101112.0	40070
			Fan 2	3660	0	Nominal	Falls	Chassis	FOW	: Suppry	P GIE LITK	SIDEVIEW					0
			Fan 3	3600	0	Nominal	[1	- 11
			Fan 4	3780	0	Nominal				Sens	sor	Sensor Value	Alarm	Occurred			- 11
	Ea	n Trav 1	Fan 5	3720	0	Nominal				External	Temp 1	28.00 °C	O N	ominal			- 11
	10	ii iiay i	Fan 7	3660	Ő	Nominal				External '	Temp 2	32.00 °C	O N	ominal			- 11
			Fan 8	3720	ŏ	Nominal				External -	Temp 3	30.00 °C	O N	ominal			
			Fan 9	3660	0	Nominal				External .	Temp 4	43.00 °C	Õ N	ominal			
	m	Keysiah	t M9506A AX	(le Chassis SFI	210210			Chase	sis	Backplane	Temp 1	23.00 °C		ominal			
								Tempera	ature	Backplane	Temp 2	25.00 °C		ominal			- 11
	File	e Utilitie	es Tools	Help						Backplane	Tomp 2	25.00 °C		ominal			
_		Turn On l	ndicator Ligh	ıt						Manageria	- Temp 3	20.00 C					
	<u> </u>		Ohanaia	Davies Oversla	DOI: Link	Olat View				Mezzanin	e remp	35.00 °C		ominal			
		-ans	Chassis	Power Supply	PCIe LINK	Slot View				Power Boar	d Temp 2	31.00 °C	O N	ominal			
		Γ					-			Volsenso	r1 1.8V	1.8 V	N	ominal			
										Volsenso	r2 1.8V	1.8 V	O N	ominal			
				<u>0</u>	utput	Value				Volsenso	r3 1.8V	1.8 V	N	ominal			
				PS	U VOUT	51.8 V				Volsenso	r4 1.8V	1.8 V	O N	ominal			
			Dannar Cr	PS	U IOUT	2.60 A							~			_	~
			Power St Unit	лрріу 1 _{DS} i	LTemp	46.00 °C		Nominal									
				P3	o remp	40.00 C		Nomina									
				PS	SU VIN	245.0 V	C) Nomina									

Figure 7. Chassis monitoring SFP



Figure 8. Trigger SFP

Technical Specifications and Characteristics

	General Chassis Characteristics					
	Standards Compliance					
AXIe-1 Revision 3.0						
	Backplane					
Instrument module slots	5					
AXIe system module	Embedded					
ESM slot configuration	x16					
AXIe instrument slot configuration	x16	x16				
Backplane speed PCIe revision 3.0 (Gen 3)						
	Mechanical					
Size	482 mm W x 195 mm H x 497 mm	D (with bumpers)				
	449 mm W x 177 mm H x 497 mm	D (with bumpers removed)				
	4U x 1 rack width					
Weight (without modules)	23.5 kg (51.8 lbs)					
	Power Supply Characteristics					
	AC Input					
Operating voltage/power ¹	20/240 V, 2000 W (maximum)					
Input frequency range 50/60 Hz						
Over current protection Auto-recovery						
DC output						
DC output voltage	52 V					
Maximum ripple and noise	500 mV pk-pk					
Instrument Module DC Output Power Characteristics	100/120 V AC	220/240 V AC				
Maximum DC output power	940 W	1500 W				
Maximum DC output current	18.0 A	28.8 A				
	Power dissipation, instrument slot					
100/120 V	300 W ^{2, 3}					
220/240 V	300 W ³					
	Chassis Cooling					
Slot airflow direction	Right to Left					
Chassis cooling intake	Right side of chassis					
Chassis cooling exhaust						
Chassis cooling fans	Six 90 cfm intake fans and six 90 cfm exhaust fans					

Auto switching between 100/120V and 220/240V. Limit total slot power dissipation to 940 W when using 100/120 VAC (a maximum of three slots dissipating 300 W each are 1. 2. supported).

A maximum per slot dissipation of 300W at 40 °C and 1500 m will result in a ≤15oC module temperature rise. At 50 °C and 3000 m, module temperature rise will be ≤18 °C. 3.

Clocks and Triggers					
100 MHz System Clock (CLK100)					
Maximum slot-to-slot skew	100 ps				
Accuracy	±30 ppm				
Input impedance	50 Ω				
IXA	e Differential Star Trigger (STRIG)				
Maximum slot-to-slot skew	100 ps				
E	xternal Clock Out (10 MHz Out)				
Connector	SMB				
Output frequency	10 MHz ±30 ppm				
Output level	3.3 V, AC coupled				
Output impedance	50 Ω				
	External Clock In (10 MHz In)				
Connector	SMB				
Frequency input	10 MHz ±100 ppm				
Input level	5 V pk-pk, AC coupled				
Minimum swing	250 mV				
Input impedance	50 Ω				
Ex	ternal Triggers (Trig1 and Trig2)				
Connectors	SMB				
Direction	Programmable				
Output level	3.3 V CMOS				
Output impedance (push-pull)	50 Ω				
Output impedance (open-drain)	316 Ω pulled up to 3.3 volts				
Input level	±5 V, adjustable threshold				
Input impedance	50 Ω or 3 kΩ (programmable)				
Minimum input swing	250 mV				
	GPS Option				
Receiver	U-Blox LEA-M8F				
Supported systems	GPS (L1), GLONASS (L1), and BeiDou (B1)				
PPS accuracy	≤ 20 ns Clear sky				
Tracking sensitivity	-165 dBm (GPS, GLONASS), -160 dBm (BeiDou)				
Sensitivity (cold start)	-148 dBm (GPS), -145 dBm (GLONASS), -138 dBm (BeiDou)				
Required antenna type	3.3V Active Antenna				
Active antenna recommendations	Minimum gain: 15 dB				
	Maximum gain: 30 dB Maximum noise figure: 1.5 dB				
Antenna connector	SMB				



Environmental Characteristics 1,2

Operating and Storage Conditions	Operating		Storage			
Temperature	0 °C to 50 °C	-40 °C to 70	O° C			
Altitude	Up to 3000 m	Up to 4600	Up to 4600 m			
Maximum Relative Humidity (non- condensing)	Type tested, 95%RH up to 40°C, decreases linearly to 45%RH at 50 °C $^{\rm 3}$					
Vibration						
Operating random vibration: type-tested at 5 to 500 Hz, 0.21 g rms						
Survival random vibration: type-tested at 5 to 500 Hz, 2.09 g rms						
Acoustical Emissions (referenced to 1 pW)	Typical Emissi	Typical Emissions at Different Cooling Loads per Slot ⁵				
	200 W	250 W	300 W ⁶			
Sound pressure level ⁴	60.8 dBA	64.5 dBA	71.0 dBA			
Sound power	68.0 dBA	70.9 dBA	72.5 dBA			

Regulatory Characteristics

Safety

Complies with the essential requirements of the European LVD Directive of the following standards (dates and editions are cited in the Declaration of Conformity):

- IEC/EN 61010-1 •
- Canada: CSA C22.2 No. 61010-1 ٠
- USA: UL std no. 61010-1 ٠

Acoustic Statement (European Machinery Directive)

Acoustic noise emission LpA < 70 dB

Operator position

Normal operation mode per ISO 7779

- Samples of this product have been type tested in accordance with the Keysight Environmental Test Manual and verified to be robust against the environmental stresses of storage, transportation and end -use. Those stresses include but are not limited to temperature, humidity, shock, vibration, altitude and power line conditions.
 Test Methods are aligned with IEC 60068 -2 and levels are similar to MIL-PRF-28800F Class 3.
 From 40 °C to 50 °C, the maximum % Relative Humidity follows the line of constant dew point.

- At operator position.
 At sea-level and 25 °C ambient temperature.
- 6. Maximum fan speed.

Regulatory Characteristics

EMC

Complies with European EMC Directive of the following standards (dates and editions are cited in the Declaration of Conformity):

- IEC/EN 61326-1
- CISPR pub 11 group 1, class A
- AS/NZS CISPR 11
- ICES/NMB-001

This ISM device complies with Canadian ICES-001. Cet appareil ISM est conforme a la norme NMB-001 du Canada.

Definitions for Specifications

Specification (spec)

Warranted performance. Specifications include guardbands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions. All specifications and characteristics apply over the operating environment outlined in the "Environmental and Regulatory" section of this data sheet. In addition, the following conditions must be met:

- Instrument is within its calibration cycle if calibration is required.
- Instrument has been stored for a minimum of 1 hour within the operating temperature range prior to turn-on and after a 30-minute warm-up period.

Characteristics

Characteristics describe product performance that is useful in the application of the product, but that is not covered by the product warranty. Characteristics are often referred to as Typical or Nominal values.

Typical (typ)

Expected performance of an average unit when operated over a 20 to 30 °C temperature range. Typical performance is not warranted. The instrument must be within its calibration cycle if calibration is required.

Nominal (nom)

Nominal describes representative performance that is useful in the application of the product when operated over a 20 to 30 °C temperature range. Nominal performance is not warranted.

Additional Information

All data are measured from multiple units at room temperature and are representative of product performance within the operating temperature range unless otherwise noted.

The data contained in this document is subject to change.

Configuration

Configure the Keysight M9506A AXIe chassis as follows:

- 1. Select the appropriate power cord based on the country where the chassis will be used. If this is North America, Japan, or Taiwan, there are two choices (100 - 120 V and 200 - 240 V). If more than 940 W are required based on the AXIe modules used, then the chassis must be operated on 200 - 240 VAC and the appropriate power cord should be selected.
- 2. Select control approach:
 - If an embedded controller is required, select an AXIe embedded controller (Keysight M9537A is recommended)
 - If an external computer is being used, select an appropriate PC interface card (Keysight M9048B/M9049A are recommended)
 - If SCPI over LAN for digitizers is required, select option -BC1
- 3. Select an appropriate cable to connect the computer interface board to the chassis interface (the Y1202A is recommended to connect the M9048B and M9022A)
- 4. Order an Y1221A AXIe Filler Module for each chassis slot which will be empty once the AXIe modules are installed. AXIe Filler Modules are not included with the chassis.
- 5. If the chassis is going to be rack-mounted, order the Y1227A rack mount kit (Figure 7)



6. Select other accessories as required

Figure 9. Y1227A Rack Mount Kit

Multi-chassis Configuration

The M9506A can be used in multi-chassis configurations with other AXIe chassis and PXIe Chassis (such M9019A). The number of chassis that can be interconnected depends on the controller and operating system used. See Tested PC and PXI/AXIe Chassis Configurations (5990-7632EN) Technical Overview for more details.

Ordering Information

Software

Supported Software Components				
Operating systems	Microsoft Windows 7 (32/64-bit), Microsoft Windows 8 (32/64-bit)			
	Microsoft Windows 10 (32/64-bit)			
Standard compliant drivers	IVI.NET, IVI-C, LabVIEW, MATLAB			
Application development environments (ADE)	Visual Studio (VB.NET, C#, C/C++), LabVIEW, LabWindows/CVI, VEE			
Keysight IO libraries	Version 2018 update 1 (or greater)			

Hardware

Model	Description				
M9506A	AXIe chassis: 5-slot, Gen 3, Embedded System Module				
	AXIe Filler Modules are not included				
M9506A-BC1	Integrated Backside Controller for Digitizer Modules ¹				
M9506A-GP1	Enable GPS				
Accessories					
Y1221A	AXIe Filler Module				
Y1227A	M9506A rack mount kit				
Related products					
M9537A	Embedded AXIe controller				
M9048B and M9049A	PCIe host adapter: Gen 3, x8 or x16				
Y1202A	PCIe cable: x8, 2.0 m				

1. Option -BC1 only supports M9703B, M9710A, M9709A digitizers.

AXIe is a registered trademark of the AXIe Consortium. PCI-SIG[®], PCI Express[®], and PCIe[®] are registered trademarks of PCI -SIG. Thunderbolt and the Thunderbolt logo are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

Learn more at: www.keysight.com

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

