





### DS730MG Technical Specification




6mm\_25T Output Shaft Spline



#### 1. Operating Data

Rated Voltage	DC7.4V
Voltage Range	DC6.0V-8.4V
Stalling Torque	26.0 Kgf.cm@6.0V
	32.0 Kgf.cm@7.4V
	40.0 Kgf.cm@8.4V
No-load Speed	0.15sec/60°@6.0V
	0.13sec/60°@7.4V
	0.11sec/60°@8.4V
Working Frequency	1520us/333Hz
Default Travel Angle	±50°=100° Total
Temperature Range	-10℃ .....+65℃
Soft Start	Programmable
Programmable	Yes
Case Material	Aluminum Alloy
Motor Type	Coreless DC Motor
Gear Set Material	Hardened Steel
Position Sensor	Potentiometer
Ball Bearing	2BB
Case Dimensions	40.5*20*38mm ±0.2mm
Weight	70g±10%

#### 2. Performance



#### 3. PWM Command signal

Signal Voltage	HIGH: min.3.3V, max.5.0V Low: min.0.0V, max.1.5V
Pulse Lengths	900us-2100us
Pulse Lengths for Position	1000us/1500us/2000us -50° 0°/+50°

#### 4. Electrical Connection

Pin Assignment				
 3 2 1	1	Orange	Signal	PWM Command
	2	Red	DC+	Supply Voltage
	3	Brown	DC	Supply Ground