




X20-2208 V2.0 Technical Specification




25T-6mm
Output Shaft Spline



1. Operating Data

Rated Voltage	DC7.4V
Voltage Range	DC6.0V-8.4V
Torque	18Kgf.cm@6.0V
	22Kgf.cm@7.4V
	25Kgf.cm@8.4V
Speed	0.09sec/60°@6.0V
	0.08sec/60°@7.4V
	0.07sec/60°@8.4V
Working	1520us/333Hz
Default Travel	± 50°=100°Total
Temperature	-20℃+65℃
Case Material	Aluminum Alloy
Motor Type	Brushless DC Motor
Gear Set Material	Hardened Steel
Position Sensor	Potentiometer
Ball Bearing	2 BB
Case Dimensions	40.5*20*38mm±0.2mm
Weight	72g±10%

2. Performance



3. Command signal

PWM Command Interface

Signal Voltage	TTL-level: HIGH: min.3.3V, max.5.0V Low: min.0.0V, max.1.5V
Pulse Lengths	900us-2100us
Pulse Lengths for Position	1000us/1500us/2000us -50°/ 0°/+50°

4. Electrical Connection

Pin Assignment (PWM)				
	1	Yellow	SIG	Command Signal
	2	Red	DC+	Supply Voltage
	3	Brown	DC-(GND)	Supply Ground, Signal Ground