

100V P-Channel Enhancement Mode MOSFET

Description

The CP35P10D6 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features

- ◆ $V_{DS} = -100V$, $I_D = -35A$
 $R_{DS(ON)}(Typ.) = 41m\Omega$ @ $V_{GS} = -10V$
 $R_{DS(ON)}(Typ.) = 44m\Omega$ @ $V_{GS} = -4.5V$
- ◆ Lead free product is acquired
- ◆ Surface mount package
- ◆ High power and current handling capability

Application


- ◆ Load switch
- ◆ BLDC Motor driver

Package

- ◆ PDFN5*6-8L-A




Schematic diagram




Marking and pin assignment

PDFN5*6-8L-A



Top View



Bottom View

XXXX—Wafer Information

YYYY—Quality Code

Ordering Information

Part Number	Storage Temperature	Package	Devices Per Reel
CP35P10D6-G	-55°C to +150°C	PDFN5*6-8L-A	5000

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

parameter		symbol	limit	unit
Drain-source voltage		V_{DS}	-100	V
Gate-source voltage		V_{GS}	±20	V
Continuous Drain Current	TC=25°C	I_D	-35	A
	TC=100°C		-24	
Pulsed Drain Current		I_{DP}	140	A
Avalanche energy(L=0.5mH)		EAS	150	mJ
Maximum power dissipation	TC=25°C	P_D	85	W
	TC=100°C		35	
Operating junction Temperature range		T_j	-55—150	°C

Electrical Characteristics (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	BV _{DSS}	V _{GS} =0V, I _D =-250μA	-100	-	-	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =-100V, V _{GS} =0V	-	-	-25	μA
		V _{DS} =-100V, V _{GS} =0V, T _J =150°C	-	-	-100	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V	-	-	±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-1.5	-2.0	-2.5	V
Drain-source on-state resistance ¹	R _{DS(ON)}	V _{GS} =-10V, I _D =-20A	-	41	50	mΩ
		V _{GS} =-4.5V, I _D =-10A	-	44	55	
On Status Drain Current	I _{D(ON)}	V _{DS} =-50V, V _{GS} =-10V	-35	-	-	A
Diode Characteristics						
Diode Forward Voltage ¹	V _{SD}	I _{SD} =-20A, V _{GS} =0V	-	-0.8	-1.3	V
Diode Continuous Forward Current	I _S		-	-35	-	A
Reverse Recovery Time	t _{rr}	I _F =-206A,	-	50	-	ns
Reverse Recovery Charge	Q _{rr}	dI/dt=-100A/us	-	65	-	nC
Dynamic Characteristics²						
Gate Resistance	R _G	V _{GS} =0V, V _{DS} =0V, f=1MHz	-	11	-	Ω
Input capacitance	C _{ISS}	V _{GS} =0V, V _{DS} =-50V f=1.0MHz	-	4092	-	pF
Output capacitance	C _{OSS}		-	163	-	
Reverse transfer capacitance	C _{RSS}		-	113	-	
Turn-on delay time	t _{D(ON)}	V _{GS} =-10V, V _{DS} =-50V, R _D =2.4Ω, I _D =-16A, R _G =9.1Ω	-	14	-	ns
Turn-on Rise time	t _r		-	42	-	
Turn-off delay time	t _{D(OFF)}		-	98	-	
Turn-off Fall time	t _f		-	75	-	
Total gate charge	Q _g	V _{GS} =-10V, I _D =-20A V _{DS} =-50V	-	76	-	nC
Gate-source charge	Q _{gs}		-	13.8	-	
Gate-drain charge	Q _{gd}		-	14.1	-	







Note: 1: Pulse test; pulse width ≤ 300ns, duty cycle ≤ 2%.



2: Guaranteed by design, not subject to production testing.

Thermal Characteristics

Parameter	Symbol	Typical	Unit
Thermal Resistance-Junction to Case	R _{θjc}	1.8	°C/W
Thermal Resistance-Junction to Ambient	R _{θja}	65	

Typical Performance Characteristics



Fig1 Output Characteristics

Fig2 Transfer Characteristics

Fig3 $R_{DS(on)}$ -Drain current

Fig4 Capacitance vs V_{DS}

Fig5 $R_{DS(on)}$ -Gate Drain voltage

Fig6 Gate Charge




Package Information

- PDFN5*6-8L-A


Top View



Bottom View



Side View



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.870	0.900	0.930	0.034	0.035	0.036
A3	0.203REF.			0.008REF.		
D	4.944	5.020	5.096	0.195	0.198	0.201
E	5.974	6.050	6.126	0.235	0.238	0.241
D1	3.910	4.010	4.110	0.154	0.158	0.162
E1	3.375	3.475	3.575	0.133	0.137	0.141
D2	4.870	4.900	4.930	0.192	0.193	0.194
E2	5.720	5.750	5.780	0.226	0.227	0.228
k	1.190	1.290	1.390	0.047	0.051	0.055
b	0.350	0.380	0.410	0.014	0.015	0.016
e	1.270TYP.			0.050TYP.		
L	0.559	0.635	0.711	0.022	0.025	0.028
L1	0.424	0.500	0.576	0.017	0.020	0.023
H	0.574	0.650	0.726	0.023	0.026	0.029
θ	10°	11°	12°	10°	11°	12°
Φ	1.150	1.200	1.250	0.045	0.047	0.049